



Confirmation of Product Type Approval

Please refer to the "Service Restrictions" shown below to determine if Unit Certification is required for this product. This certificate reflects the information on the product in the ABS Records as of the date and time the certificate is printed.

Pursuant to the Rules of the American Bureau of Shipping (ABS), the manufacturer of the below listed product held a valid Manufacturing Assessment (MA) with expiration date of 23-FEB-2022. The continued validity of the Manufacturing Assessment is dependent on completion of satisfactory audits as required by the ABS Rules.

And; a Product Design Assessment (PDA) valid until subject to continued compliance with the Rules or standards used in the evaluation of the product.

The above entitle the product to be called Product Type Approved.

The Product Design Assessment is valid for products intended for use on ABS classed vessels, MODUs or facilities which are in existence or under contract for construction on the date of the ABS Rules used to evaluate the Product.

ABS makes no representations regarding Type Approval of the Product for use on vessels, MODUs or facilities built after the date of the ABS Rules used for this evaluation.

Due to wide variety of specifications used in the products ABS has evaluated for Type Approval, it is part of our contract that; whether the standard is an ABS Rule or a non-ABS Rule, the Client has full responsibility for continued compliance with the standard.

Product Name: Cable, Electric Control and Communication Cables
Model Name(s): FM2XCCH, FM2XAH, FM2XAAH

Presented to:

UNTEL KABLOLARI SANAYI VE TICARET ANONIM SIRKETI
MAKINE OSB, 6.CAD. NO: 4 41455
DILOVASI-GEBZE
Turkey

Intended Service:	Communication and signal cables for Shipboard Applications. Not intended for use as propulsion cable.
Description:	FM2XCCH halogen-free, flame retardant, individually and overall screened, communication and signal cable, FM2XAH halogen-free, flame retardant, communication and signal cable, FM2XAAH halogen-free, flame retardant, individually and overall screened, communication and signal cable, Insulation: XLPE Conductor: Electrolytic, stranded, annealed copper wire. IEC 60228 Class 2 (Class 5 and/or tinned on request) Outer Sheath: Halogen-free, flame retardant thermoplastic polyolefin based compound (SH1)
Tier:	3
Ratings:	Voltage grade: 60/250V Maximum operating temperature: 90 deg. C Lowest ambient temperature for fixed installation: -40 deg. C
Service Restrictions:	Unit Certification is not required for this product. If the manufacturer or purchaser request an ABS Certificate for compliance with a specification or standard, the specification or standard, including inspection standards and tolerances, must be clearly defined.
Comments:	The following cable markings are to be provided in accordance with IEC 60092-353: Indication of origin (manufacturer's name or trade mark) and rated voltage (Uo/ U) and construction (number of cores and cross sectional area of the

conductor). The Manufacturer has provided a declaration about the control of, or the lack of Asbestos in this product.

Notes / Documentation:

Drawing No. FM2XCCH-FM2XAH-FM2XAAH Data Sheets, FR 70-023, FR 70-024, Revision: 0, Drawing No. FM2XCCH-FM2XAH-FM2XAAH Untel Test Report dated 10.08.2016, Revision: 0, Drawing No. FM2XCCH-FM2XAH-FM2XAAH Common Tests Specification dated 10.08.2016, Revision: 0

Term of Validity:

This Product Design Assessment (PDA) Certificate 17-GD1602617-PDA, dated 24/Feb/2017 remains valid until 23/Feb/2022 or until the Rules or specifications used in the assessment are revised (whichever occurs first). This PDA is intended for a product to be installed on an ABS classed vessel, MODU or facility which is in existence or under contract for construction on the date of the ABS Rules or specifications used to evaluate the Product. Use of the Product on an ABS classed vessel, MODU or facility which is contracted after the validity date of the ABS Rules and specifications used to evaluate the Product, will require re-evaluation of the PDA. Use of the Product for non ABS classed vessels, MODUs or facilities is to be to an agreement between the manufacturer and intended client.

ABS Rules:

Steel Vessel Rules (2017): 1-1-4/7.7, 1-1-A3 & A4, 4-8-3/9.1, 4-8-3/9.3, 4-8-3/9.5, 4-8-3/9.9 Steel Vessels Under 90 Meters (295 Feet) in Length (2017): 1-1-4/7.7, 1-1-A3 & A4, 4-6-4/13.1.1, 4-6-4/13.1.2, 4-6-4/13.1.4 Offshore Support Vessels (2017): 1-1-4/7.7, 1-1-A3 & A4, 4-8-3/9.1, 4-8-3/9.3, 4-8-3/9.5, 4-8-3/9.9 Steel Vessels for Service on Rivers and Intracoastal Waterways (2017): 1-1-4/7.7, 1-1-A3 & A4, 4-5-4/13.1.1, 4-5-4/13.1.2, 4-5-4/13.1.4, 4-5-4/13.1.5 High-Speed Craft (2017): 1-1-4/11.9, 1-1-A2 & A3, 4-6-4/13.1.1, 4-6-4/13.1.2, 4-6-4/13.1.4, 4-6-4/13.1.5 Steel Barge Rules (2017): 1-1-4/7.7, 1-1-A3 & A4

**National Standards:
International Standards:**

IEC 60092-376 (2003), IEC 60092-350 (2014), IEC 60092-351 (2004), IEC 60092-353 (2011), IEC 60092-360 (2014), IEC 60092-351 (2014), IEC 60332-1 (2004), IEC 60332-3-22 (2009) (Cat A), IEC 61034 (2013), IEC 60754-1 (2011), IEC 60754-2 (2011),

Government Authority:

EUMED:

Others:

Model Certificate	Model Certificate No	Issue Date	Expiry Date
PDA	17-GD1602617-PDA	24-FEB-2017	23-FEB-2022



ABS Programs

ABS has used due diligence in the preparation of this certificate and it represents the information on the product in the ABS Records as of the date and time the certificate was printed. Type Approval requires Drawing Assessment, Prototype Testing and assessment of the manufacturer's quality assurance and quality control arrangements. Limited circumstances may allow only Prototype Testing to satisfy Type Approval. The approvals of Drawings and Products remain valid as long as the ABS Rule, to which they were assessed, remains valid. ABS cautions manufacturers to review and maintain compliance with all other specifications to which the product may have been assessed. Further, unless it is specifically indicated in the description of the product; Type Approval does not necessarily waive witnessed inspection or survey procedures (where otherwise required) for products to be used in a vessel, MODU or facility intended to be ABS classed or that is presently in class with ABS. Questions regarding the validity of ABS Rules or the need for supplemental testing or inspection of such products should, in all cases, be addressed to ABS.