

## UNT AGL SECONDARY POWER FLEX – B

**SEKONDER PİST AYDINLATMA KABLOSU – TİP B**  
*SECONDARY AIRPORT LIGHTING CABLE – TYPE B*


**ICEA S-93-659 / NEMA WC71**  
*FAA – L 824 ( AC - 150/5375-7E SPECIFICATION FOR L-824)*

### KABLO YAPISI

- \* İLETKEN : İnce çok telli Tavlı Bakır İletken (Tip TB ) veya İnce çok telli Kalaylı (Tip BB) Bakır İletken
- \* İZOLE : EPR Kauçuk
- \* DIŞ KILIF : PCP veya eşdeğeri malzeme

### CABLE STRUCTURE

- \* CONDUCTOR : Fine Strand of annealed tinned copper wires (Type TC ) or fine plain copper wires (Type BC )
- \* INSULATION : EPR Rubber
- \* OUTER JACKET : PCP or equivalent



### ÇALIŞMA KARAKTERİSTİKLERİ / OPERATING CHARACTERISTICS

- ÇALIŞMA SICAKLIĞI / CONDUCTOR OPERATING TEMPERATURE : -25 / +90°C
- ÇALIŞMA GERİLİMİ / RATED VOLTAGE : 600 V
- TEST GERİLİMİ / TEST VOLTAGE : 2 kV
- BÜKME YARI ÇAPI / BENDING RADIUS : 10 x Outer Diameter
- TEST STANDARTI / STANDARD OF TEST : FAA – L 824 AC - 150/5375-7E

Tüm kesitler AWG ve Metrik olarak sağlanabilir.  
*All sizes are available in AWG and Metric*