

## UNT AGL UNSCREENED FLEX POWER-B

**EKRANSIZ ESNEK PRİMER PİST AYDINLATMA KABLOSU – TİP B**  
*UNSCREENED FLEXIBLE PRIMARY AIRPORT LIGHTING CABLE – TYPE B*

**ICEA S-93-659 / NEMA WC71**  
*FAA – L 824 ( AC - 150/5375-7E SPECIFICATION FOR L-824)*

### KABLO YAPISI

- \* **İLETKEN** : Tavlı Bakır İletken (Tip TC ) veya Kalaylı (Tip BC ) Bakır İletken - IEC C 60228 CL 2' ye göre
- \* **YARI İLETKEN TABAKA** : Ekstruze yarı iletken tabaka - ICEA S-93-659 / NEMA WC71' e göre
- \* **İZOLE** : EPR Kauçuk - ICEA S-93-659 / NEMA WC71' e göre
- \* **DIŞ KILIF** : PCP veya eşdeğeri malzeme - ICEA S-93-659 / NEMA WC71' e göre

### CABLE STRUCTURE

- \* **CONDUCTOR** : Strand of annealed tinned copper wires (Type TC ) or plain copper wires (Type BC ) according to IEC C 60228 CL 2
- \* **SEMICONDUCTIVE LAYER** : Extruded Semiconductive material according to ICEA S-93-659 / NEMA WC71
- \* **INSULATION** : EPR Rubber according to ICEA S-93-659 / NEMA WC71
- \* **OUTER JACKET** : PCP or equivalent according to ICEA S-93-659 / NEMA WC71



### ÇALIŞMA KARAKTERİSTİKLERİ / OPERATING CHARACTERISTICS

- ÇALIŞMA SICAKLIĞI / CONDUCTOR OPERATING TEMPERATURE : -25 / +90°C
- ÇALIŞMA GERİLİMİ / RATED VOLTAGE : 5 kV
- TEST GERİLİMİ / TEST VOLTAGE : 18 kV
- BÜKME YARI ÇAPI / BENDING RADIUS : 6 x Outer Diameter
- TEST STANDARDI / STANDARD OF TEST : ICEA S-93-659 / NEMA WC71

Tüm kesitler AWG ve Metrik olarak sağlanabilir.  
*All sizes are available in AWG and Metric*