

Certificate No: **TAE000038T**

TYPE APPROVAL CERTIFICATE

This is to certify:		
That the Low Voltage	Cable	
with type designation(s) FM2XAAH		
Issued to Untel Kablolar Dilovasi, Turkey	i San. ve Tic. A.S	•
is found to comply with DNV GL rules for class	ification – Ships, offshore	units, and high speed and light craft
Application:		
Product(s) approved by DNV GL.	y this certificate is/are a	ccepted for installation on all vessels classed
Rated voltage (V) 15 Temp. class (°C) 90		
Issued at Hamburg on	2019-01-18	
This Certificate is valid u	ntil 2024-01-17 .	for DNV GL
DNV GL local station: Ist	:anbul	
Approval Engineer: Cars	ten Hunsalz	
		Arne Schaarmann
		Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Form code: TA 251 Revision: 2016-12 www.dnvgl.com Page 1 of 3

Job Id: **262.1-028904-1** Certificate No: **TAE000038T**

Product description

Halogen free, XLPE insulated and thermoplastic sheathed shipboard communication and signal cable

Type: FM2XAAH

Rated voltage: 150 / 250 V

Maximum operating conductor temperature: 90° C

Conductor: Stranded copper conductor, class 2 / 5 (tinned optional)

Insulation: XLPE

Individual screen: Aluminium tape+ drain wire Overall screen: Aluminium tape+ drain wire

Outer sheath: Thermoplastic polyolefin based compond / SHF1

Number of cores: Cross-sectional area:

1 x 2 to 4 x 2 0,5 mm ²

Application/Limitation

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

Instrumentation, communication and control.

Flame retardant in bunch Cat. A. Halogen free. Low smoke.

Type Approval documentation

Tests carried out

Standard	Release	General description	Limitation
IEC 60092-350	2014-08	General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications	
IEC 60092-376	2017-05	Cables for control and instrumentation circuits 150/250 V (300 V)	
IEC 60092-360	2014-04	Electrical installations in ships - Part 360: Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telecommunication cables.	
IEC 60332-3-22	2018-07	Tests on electric and optical fibre cables under fire conditions – Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category A	Charred portion of sample does not exceed 2,5m above bottom edge of burner.
IEC 60754-1	2011-11	Test on gases evolved during combustion of materials from cables - Part 1: Determination of the halogen acid gas content	Low Halogen: <0,5% Halogen
IEC 60754-2	2011-11	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity	Halogen free: pH > 4,3 Conductivity < 10µS/mm

Form code: TA 251 Revision: 2016-12 www.dnvgl.com Page 2 of 3

Job Id: **262.1-028904-1** Certificate No: **TAE000038T**

Standard	Release	General description	Limitation
IEC 60684-2	2011-08	Clause 45.2 Methods of determination of low levels of fluorine	HF max 0,1%
IEC 61034-1/2	2013-06	Measurement of smoke density of cables	Low smoke
		burning under defined conditions –	Light
		Test apparatus, procedure and	transmittance >60%
		requirements	

Marking of product

ÜNTEL - FM2XAAH - size - 250 V - IEC 60332-3-22

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine Tests (RT) checked (if not available tests according to RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE

Form code: TA 251 Revision: 2016-12 www.dnvgl.com Page 3 of 3